



INSTALLATION BRACKET

**NOTE**

- 1. TYPE : BRUSHLESS DC MOTOR DRIVER (XBD SERIES)
- 2. SPECIFICATION

MODEL	VOLTAGE	RATED OUTPUT	RATED SPEED (CONTROL RANGE)	APPLY MOTOR
XBD200B	SINGLE PHASE 200-230 V 50/60 Hz	200 W	3000 r/min (200 ~ 3000 r/min)	XBM10200G(D)
XBD200U	THREE PHASE 200-230 V 50/60 Hz	200 W		XBM10200G(D)
XBD400U		400 W		XBM10400G(D)

- 3. Dimension of the model(above three model) are all the same.
- 4. Applicable motor and driver must always match.
- 5. Degree of protection is IP10.
- 6. Operation environment.

- ① Temperature : 0 ~ 50 °C(+32 ~ +122°F) non-freezing
- ② Humidity : less than 85%(non-condensing)

DATE				SIGN				NOTE				REVISION			
MATERIAL				SURFACE FINISH				SCALE				TOLERANCE			
DRAWN				DESIGN				CHECK				APPR.			
Y.W. CHO 2013.04.20				Y.W. CHO 2013.04.20				S.H. CHA 2013.04.22				I.B. SHIN 2013.04.22			
NAME								BLDC DRIVER ASS'Y XBD Serise (200W/400W)							
SPG Co., Ltd.								DATE				2013.04.20			
DWG NO.															