



**NOTE**

1. TYPE : BRUSHLESS DC MOTOR DRIVER (XFD SERIES)
2. SPECIFICATION

MODEL	VOLTAGE	RATED OUTPUT	RATED SPEED (CONTROL RANGE)	APPLY MOTOR
XFD30	DC 24V	30 W	2500 r/min (200 ~ 3000 r/min)	XFM630G(D)
XFD50		50 W		XFM850G(D)

3. Dimension of the model are all the same.
4. Applicable motor and driver must always match.
5. Degree of protection is IP00.
6. Operation environment
  - ① Temperature : 0 ~ +50 °C(+32 ~ +122 °F) non-freezing
  - ② Humidity : less than 85%(non-condensing)

△									
△									
△									
DATE	SIGN	NOTE				REVISION			
MATERIAL		SURFACE FINISH		SCALE	1/1	TOLERANCE	±0.02(0.5)		
DRAWN	DESIGN	CHECK	APPR.	NAME		DRIVER ASS'Y			
Y.W.CHO 2013.04.19	Y.W.CHO 2013.04.19	S.H.CHA 2013.04.22	I.B.SHIN 2013.04.22			XFD SERIES(30W/50W)			
SPG Co., Ltd.		DATE	2013.04.19	DWG NO.					