



NOTE

- 1. TYPE : BRUSHLESS DC MOTOR DRIVER (XWD SERIES)
- 2. SPECIFICATION

MODEL	VOLTAGE	RATED OUTPUT	RATED SPEED (CONTROL RANGE)	APPLY MOTOR
XWD10A	SINGLE PHASE 100-120 V 50/60 Hz	10 W	2000 r/min (100 ~ 2000 r/min)	XWM610G(D)
XWD25A		25 W		XWM825G(D)
XWD40A		40 W		XWM940G(D)
XWD90A		90 W		XWM990G(D)
XWD10B	SINGLE PHASE 200-230 V 50/60 Hz	10 W		XWM610G(D)
XWD25B		25 W		XWM825G(D)
XWD40B		40 W		XWM940G(D)
XWD90B		90 W		XWM990G(D)

- 3. Dimension of the model are all the same.
- 4. Applicable motor and driver must always match.
- 5. Degree of protection is IP10.
- 6. Operation environment
 - ① Temperature : 0 ~ +40°C(+32 ~+104°F) non-freezing
 - ② Humidity : less than 85%(non-condensing)

△									
△									
△									
DATE	SIGN	NOTE				REVISION			
MATERIAL		SURFACE FINISH		SCALE	1/1	TOLERANCE	±0.02(0.5)		
DRAWN	DESIGN	CHECK	APPR.	NAME		BLDC DRIVER ASS'Y			
Y.W.CHO	Y.W.CHO	S.H.CHA	I.B.SHIN			XWD SERIES			
2013.04.18	2013.04.18	2013.04.22	2013.04.22				DATE	2013.04.18	DWG NO.
SPG SPG Co., Ltd.									