



▽ GEAR HEAD SPINDLE SPECIFICATIONS-(TABLE-2)

MODEL	SPECIFICATIONS (S=1/2)	KEY SPEC
STRAIGHT TYPE		
S8SA3B(B1) ~S8SA200B(B1)		
D-CUT TYPE		
S8DA3B(B1) ~S8DA200B(B1)		
KEY TYPE		
S8KA3B(B1) ~S8KA200B(B1)		

▽ \*L (TABLE-1)

GEAR RATIO	SIZE (inch [mm])
S8□A3B(B1) ~ S8□A18B(B1)	1.26 (32)
S8□A20B(B1) ~ S8□A200B(B1)	1.67 (42.5)

NOTE

1. TYPE : GEAR HEAD
2. ROTATION : VIEWED FROM SHAFT END C.W. or C.C.W.
3. END PLAY : 0.02inch (0.5mm) Max.

△									
△									
△									
DATE	SIGN	NOTE			REVISION				
MATERIAL	SURFACE FINISH		SCALE	1/1	TOLERANCE	± 0.04 [1.0]			
DRAWN	DESIGN	CHECK	APPR.	GEAR HEAD ASS'Y					
J.Y.JUNG	H.W.LEE	B.Y.JEONG	NAME						
2012.05.18	2012.05.18	2012.05.18		S8□ A□ B(B1)					
SPG MOTOR SPG Co., Ltd.			DATE	DWG NO.					